NSN 5962-00-101-8281

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-101-8281 **Body Length:** Between 0.240 inches and 0.275 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 45.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and complementary outputs and low power and medium speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 multivibrator, monostable **Case Outline Source And Designator:** T0-86 joint electron device engineering council **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Test Data Document:** 84347-g190-003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

No

Demilitarization: