NSN 5962-00-106-0836

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-106-0836 **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 800.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+165.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and high speed and negative outputs and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 switch, analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:**

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0