NSN 5962-00-106-6614

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-106-6614

view Offilite at https://defobasegroup.com/hsh/osoz-oo-100-0014
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
110.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs and edge triggered and medium power and medium speed and presettable and w/clear
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 flip-flop, j-k, and input master slave and 1 flip-flop, j-k, clocked
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Silver
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
39.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Terminal Type And Quantity:
14 printed circuit

N/a

Unit Of Measure:

Shelf Life:

NSN 5962-00-106-6614

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0