## NSN 5962-00-111-1205

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-111-1205

view Online at https://aerobasegroup.com/nsn/5962-00-111-1205
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
50.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and asynchronous and edge triggered and synchronous
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 flip-flop, pulse triggered
Case Outline Source And Designator:
T0-86 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
15.00 nanoseconds propagation delay time, low to high level output
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli

Fiig:

A458a0