NSN 5962-00-111-3628

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-111-3628 **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.050 inches and 0.065 inches **Maximum Power Dissipation Rating:** 570.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and high gain and low power and low level and negative outputs and positive outputs and externally compensated **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** T0-91 joint electron device engineering council **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -65.0 volts power source and 10.0 volts power source **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-00-111-3628 Linear Microcircuit - Page 2 of 2



Fiig:

A458a0