## NSN 5962-00-113-1266

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-113-1266

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
44.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and medium speed
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 gate, nand-nor
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

Yes - demil/mli

## **NSN 5962-00-113-1266**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0