## NSN 5962-00-117-4553

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-117-4553

| View Offiline at https://acrobasegroup.com/hsh/0502-00-117-4000  |
|--|
| Body Length:   |
| Between 0.660 inches and 0.785 inches  |
| Body Width:  |
| Between 0.220 inches and 0.280 inches  |
| Body Height:   |
| Between 0.140 inches and 0.180 inches  |
| Maximum Power Dissipation Rating:  |
| 50.0 milliwatts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and asynchronous and edge triggered and positive outputs and resettable and synchronous and w/clear |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Diode-transistor logic   |
| Input Circuit Pattern:   |
| 6 input  |
| Design Function And Quantity:  |
| 1 flip-flop, j-k/r-s, clocked, master slave and 1 flip-flop, pulse triggered   |
| Case Outline Source And Designator:  |
| T0-116 joint electron device engineering council   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -1.5 volts power source and 5.5 volts power source   |
| Time Rating Per Chacteristic:  |
| 15.00 nanoseconds propagation delay time, low to high level output   |
| Terminal Type And Quantity:  |
| 14 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |

Fiig:

A458a0