NSN 5962-00-117-4573

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-117-4573

view Online at https://aerobasegroup.com/nsn/5962-00-117-4573
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.240 inches and 0.260 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Interrogator set type an/apx-76 and an/apx-81
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, intermediate frequency and 1 amplifier, log
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Time Rating Per Chacteristic:
2.00 nanoseconds propagation delay time, low to high level output and 2.00 nanoseconds propagation delay time, high to low level output
Special Features:
Weapons system essential
Precious Material And Location:
Terminals gold
Precious Material:

80249-911167 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

Test Data Document:

8 pin

Gold

Shelf Life:

N/a

NSN 5962-00-117-4573

Linear Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0