# NSN 5962-00-117-4573

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-117-4573

# Body Outside Diameter:

Between 0.335 inches and 0.370 inches

# Body Height:

Between 0.240 inches and 0.260 inches

# Maximum Power Dissipation Rating:

500.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **End Application:**

Interrogator set type an/apx-76 and an/apx-81

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs

#### **Inclosure Material:**

# Glass and metal

Inclosure Configuration:

Can

#### **Input Circuit Pattern:**

2 input

## **Criticality Code Justification:**

Feat

## Design Function And Quantity:

1 amplifier, intermediate frequency and 1 amplifier, log

## **Terminal Surface Treatment:**

Gold

## Voltage Rating And Type Per Characteristic:

6.0 volts power source

## Time Rating Per Chacteristic:

2.00 nanoseconds propagation delay time, low to high level output and 2.00 nanoseconds propagation delay time, high to low level output

#### **Special Features:**

Weapons system essential

## **Precious Material And Location:**

Terminals gold

## **Precious Material:**

Gold

## Test Data Document:

80249-911167 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

8 pin

#### Shelf Life:

N/a

# NSN 5962-00-117-4573

Linear Microcircuit - Page 2 of 2



---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

