

View Online at <https://aerobasegroup.com/nsn/5962-00-117-6091>

Body Length:

Between 0.250 inches and 0.260 inches

Body Width:

Between 0.140 inches and 0.150 inches

Body Height:

Between 0.035 inches and 0.050 inches

Maximum Power Dissipation Rating:

160.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and medium speed and medium power and w/totem pole output

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, nand

Case Outline Source And Designator:

T0-84 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads; insulator furnished

Precious Material And Location:

Terminals gold and body gold

Precious Material:

Gold

Test Data Document:

96214-507860 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0