NSN 5962-00-120-2640

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-120-2640

Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 comparator, voltage
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
28527-2136926 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-00-120-2640

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0