NSN 5962-00-123-9305

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-00-123-9505
Body Length:
Between 0.240 inches and 0.260 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.067 inches and 0.090 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and high voltage and high speed and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 driver, high current and 1 driver, peripheral
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
220.00 nanoseconds propagation delay time, low to high level output and 160.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
10 flat leads
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Ves - demil/mli

Fiig:

A458a0