# NSN 5962-00-123-9305

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-123-9305

## **Body Length:**

Between 0.240 inches and 0.260 inches

## Body Width:

Between 0.240 inches and 0.260 inches

## **Body Height:**

Between 0.067 inches and 0.090 inches

## **Maximum Power Dissipation Rating:**

800.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed and high voltage and high speed and positive outputs

## **Inclosure Material:**

## Ceramic and glass

## Inclosure Configuration:

Flat pack

## Input Circuit Pattern:

5 input

## **Design Function And Quantity:**

1 driver, high current and 1 driver, peripheral

## **Terminal Surface Treatment:**

Gold

## Voltage Rating And Type Per Characteristic:

8.0 volts power source

## **Time Rating Per Chacteristic:**

220.00 nanoseconds propagation delay time, low to high level output and 160.00 nanoseconds propagation delay time, high to low level output

## **Precious Material And Location:**

Terminals gold

## **Precious Material:**

Gold

## **Terminal Type And Quantity:**

10 flat leads

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

## Fiig:

A458a0