NSN 5962-00-126-0490

Linear Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5962-00-126-0490
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs and negative outputs and externally compensated
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-6.0 volts power source and 1.5 volts power source
Time Rating Per Chacteristic:
120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface silver
Precious Material:
Silver
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-00-126-0490

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0