NSN 5962-00-130-8933

Digital Microcircuit - Page 1 of 1



level output and 50.00 nanoseconds propagation delay time, high to low level

View Online at https://aerobasegroup.com/nsn/5962-00-130-8933

Body Length:	
0.390 inches	
Body Width:	
Between 0.235 inches and 0.260 inches	
Body Height:	
Between 0.045 inches and 0.085 inches	
Maximum Power Dissipation Rating:	
220.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and monolithic and w/clear and w/clock	C
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Flat pack	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
Dual 4 input	
Design Function And Quantity:	
2 generator, baud rate	
Case Outline Source And Designator:	
F-2 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
-0.5 volts power source and 7.0 volts power source	
Time Rating Per Chacteristic:	
39.00 nanoseconds propagation delay time, low to high level output a	n
putput	
Terminal Type And Quantity:	
14 flat leads	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	

A458a0