

View Online at <https://aerobasegroup.com/nsn/5962-00-133-4263>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.240 inches and 0.260 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+165.0 degrees celsius

Features Provided:

Hermetically sealed and hybrid and negative outputs and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 switch, analog

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

10.0 volts power source

Time Rating Per Characteristic:

700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

24930-g390078 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0