

View Online at <https://aerobasegroup.com/nsn/5962-00-135-7061>

Body Length:

Between 0.250 inches and 0.260 inches

Body Width:

Between 0.140 inches and 0.150 inches

Body Height:

Between 0.035 inches and 0.050 inches

Maximum Power Dissipation Rating:

52.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/totem pole output

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 gate, nand buffer

Case Outline Source And Designator:

T0-84 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

22.00 nanoseconds propagation delay time, low to high level output

Special Features:

Formed leads

Precious Material And Location:

Terminals gold and body gold

Precious Material:

Gold

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0