## NSN 5962-00-136-3221

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-136-3221

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
46.5 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and edge triggered and low power and medium speed and resettable and w/clea
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 flip-flop, j-k/r-s, clocked
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0