

View Online at <https://aerobasegroup.com/nsn/5962-00-137-3551>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

250.0 milliwatts

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Storage Temperature Range:**

-55.0/+150.0 degrees celsius

**Features Provided:**

W/clock and hermetically sealed and monolithic

**Inclosure Material:**

Metal

**Inclosure Configuration:**

Can

**Output Logic Form:**

P-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

Dual 2 input

**Design Function And Quantity:**

2 shift register, static

**Case Outline Source And Designator:**

To-100 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

6.0 volts power source

**Time Rating Per Characteristic:**

200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

10 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0