NSN 5962-00-137-5004

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-137-5004

View Online at https://aerobasegroup.com/nsn/5962-00-137-5004
Body Length:
Between 0.310 inches and 0.365 inches
Body Width:
Between 0.235 inches and 0.275 inches
Body Height:
Between 0.035 inches and 0.080 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and high speed and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 driver, clock
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
09128-d34000578 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A458a0

Demilitarization: Yes - demil/mli