

View Online at <https://aerobasegroup.com/nsn/5962-00-137-5043>

Body Length:

Between 0.550 inches and 0.650 inches

Body Width:

Between 0.300 inches and 0.400 inches

Body Height:

Between 0.008 inches and 0.120 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and medium speed and asynchronous and synchronous and expandable and w/strobe

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Current-mode logic

Input Circuit Pattern:

Dual 9 input

Design Function And Quantity:

2 comparator

Case Outline Source And Designator:

-0-019-aa joint electron device engineering council

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

13499-351-1025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0