NSN 5962-00-137-8928

Digital Microcircuit - Page 1 of 1



to low level

View Online at https://aerobasegroup.com/nsn/5962-00-137-8928

Bod	ly Length:	
0.78	35 inches	
Bod	ly Width:	
0.29	01 inches	
Bod	ly Height:	
0.19	90 inches	
Мах	kimum Power Dissipation Rating:	
300.	.0 milliwatts	
Оре	erating Tempurature Range:	
+0.0	0/+75.0 degrees celsius	
Stor	rage Tempurature Range:	
-65.	0/+150.0 degrees celsius	
Fea	tures Provided:	
Mon	nolithic and hermetically sealed and asynchronous and resettable and w/enable	
Incl	osure Material:	
Plas	stic	
Incl	osure Configuration:	
Dua	ıl-in-line	
Out	put Logic Form:	
Trar	nsistor-transistor logic	
Inpu	ut Circuit Pattern:	
9 inp	put	
Des	sign Function And Quantity:	
1 sh	nift register, universal	
Terr	minal Surface Treatment:	
Solo	der	
Volt	tage Rating And Type Per Characteristic:	
5.5	volts power source	
Tim	e Rating Per Chacteristic:	
22.0	00 nanoseconds propagation delay time, low to high level output and 26.00 nanoseconds propagation delay time, h	high t
outp	but	
Terr	minal Type And Quantity:	
16 p	printed circuit	
She	elf Life:	
N/a		
Unit	t Of Measure:	
Den	nilitarization:	
Yes	- demil/mli	
Fiig	r.	
A45	8a0	