NSN 5962-00-138-1525

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-138-1525

View Online at https://aerobasegroup.com/nsn/5962-00-138-1525
Body Length:
Between 0.371 inches and 0.409 inches
Body Width:
Between 0.247 inches and 0.283 inches
Body Height:
Between 0.050 inches and 0.075 inches
Maximum Power Dissipation Rating:
145.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 decoder, one of ten line
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
92220511-040 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-00-138-1525

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0