

View Online at <https://aerobasegroup.com/nsn/5962-00-140-6432>

**Body Length:**

Between 0.240 inches and 0.390 inches

**Body Width:**

Between 0.120 inches and 0.270 inches

**Body Height:**

Between 0.035 inches and 0.090 inches

**Maximum Power Dissipation Rating:**

150.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and hybrid and positive outputs and negative outputs

**Inclosure Material:**

Ceramic and metal

**Inclosure Configuration:**

Flat pack

**Input Circuit Pattern:**

2 channel

**Design Function And Quantity:**

1 driver, switch, field effect transistor

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

10.0 volts power source

**Time Rating Per Characteristic:**

200.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold and body gold

**Precious Material:**

Gold

**Test Data Document:**

99974-st8596938 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0