## NSN 5962-00-145-3735

Linear Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5962-00-145-3735
Body Length:
Between 2.470 inches and 2.530 inches
Body Width:
Between 1.720 inches and 1.780 inches
Body Height:
Between 0.350 inches and 0.410 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and negative outputs and positive outputs
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 multiplier, analog
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
1500.00 nanoseconds propagation delay time, low to high level output and 2000.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
12115-sc5962-0023 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
9 printed circuit
Shelf Life:
N/a

Yes - demil/mli

**Unit Of Measure:** 

Demilitarization:

## **NSN 5962-00-145-3735** Linear Microcircuit - Page 2 of 2



Fiig:

A458a0