## NSN 5962-00-147-2084

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-147-2084
Body Length:
Between 1.780 inches and 1.800 inches
Body Width:
Between 1.180 inches and 1.200 inches
Body Height:
Between 0.580 inches and 0.600 inches
Maximum Power Dissipation Rating:
950.0 milliwatts
Operating Tempurature Range:
-18.0/+71.0 degrees celsius
Storage Tempurature Range:
-54.0/+85.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and negative outputs and positive outputs and adjustable
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, operational, instrumentation
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
16.2 volts power source
Time Rating Per Chacteristic:
600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
18876-11156830 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
9 printed circuit
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## **NSN 5962-00-147-2084** Linear Microcircuit - Page 2 of 2



Fiig:

A458a0