

View Online at <https://aerobasegroup.com/nsn/5962-00-147-4456>

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

120.0 milliwatts

Operating Temperature Range:

+0.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and medium power and medium speed and w/totem pole output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Triple 3 input

Design Function And Quantity:

3 gate, nand

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

00752-373405 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0