# NSN 5962-00-147-4494

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-147-4494

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

54.5 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and medium speed and expandable

## **Inclosure Material:**

# Ceramic and glass

# Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

Diode-transistor logic

## Input Circuit Pattern:

5 input

## **Design Function And Quantity:**

2 gate, nand-nor

## Case Outline Source And Designator:

T0-116 joint electron device engineering council

## **Time Rating Per Chacteristic:**

50.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

98738-221g3108 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0