NSN 5962-00-156-5761



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-156-5761 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** 0.145 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 1 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** To-116 joint electron device engineering council **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:**

Shelf Life:

N/a

Unit Of Measure:

14 printed circuit

Demilitarization:

Yes - demil/mli

NSN 5962-00-156-5761

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0