NSN 5962-00-156-5765

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-156-5765

Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
85.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and w/expander and w/resistor and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 buffer
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
80.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A458a0

Demilitarization: Yes - demil/mli