NSN 5962-00-158-4940

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-158-4940

| View Online at https://aerobasegroup.com/nsn/5962-00-158-4940 |
|--|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 255.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+175.0 degrees celsius |
| Features Provided: |
| High speed and monolithic and presettable and resettable and w/strobe and positive outputs |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 8 input |
| Design Function And Quantity: |
| 1 counter |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 42.00 nanoseconds propagation delay time, low to high level output and 42.00 nanoseconds propagation delay time, high to low level |
| output |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0