

View Online at <https://aerobasegroup.com/nsn/5962-00-160-5028>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and edge triggered and medium speed and positive outputs and w/clear and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 flip-flop, clocked and 2 flip-flop, j-k, master slave

**Case Outline Source And Designator:**

T0-116 joint electron device engineering council

**Time Rating Per Characteristic:**

25.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0