NSN 5962-00-160-5590

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-160-5590
Body Length:
Between 0.250 inches and 0.260 inches
Body Width:
Between 0.140 inches and 0.150 inches
Body Height:
Between 0.035 inches and 0.050 inches
Maximum Power Dissipation Rating:
16.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and 1-phase
Inclosure Material:
Glass and metal
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Case Outline Source And Designator:
T0-84 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold and body gold
Precious Material:
Gold
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-00-160-5590

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0