NSN 5962-00-163-0135

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5062-00-163-0135

| View Online at https://aerobasegroup.com/nsn/5962-00-163-0135 |
|--|
| Body Length: |
| Between 0.815 inches and 0.890 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.155 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 350.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and positive outputs and programmable and synchronous and w/clear and w/enable and w/strobe |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 11 input |
| Design Function And Quantity: |
| 1 multiplier, binary and 1 multiplier, rate |
| Case Outline Source And Designator: |
| -0-001-al joint electron device engineering council |
| Terminal Surface Treatment: |
| Silver |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Precious Material And Location: |
| Terminals silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

NSN 5962-00-163-0135Digital Microcircuit - Page 2 of 2



Fiig:

A458a0