# NSN 5962-00-163-0143

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-163-0143 **Body Length:** Between 0.815 inches and 0.890 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.155 inches and 0.180 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and positive outputs and asynchronous and edge triggered and presettable and programmable and synchronous and w/enable **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 8 input **Case Outline Source And Designator:** -0-001-al joint electron device engineering council **Terminal Surface Treatment:** Silver **Voltage Rating And Type Per Characteristic:** 

-1.5 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

42.00 nanoseconds propagation delay time, low to high level output and 52.00 nanoseconds propagation delay time, high to low level output

#### **Precious Material And Location:**

Terminals silver

#### **Precious Material:**

Silver

## **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

### **Unit Of Measure:**

#### Demilitarization:

Yes - demil/mli

# **NSN 5962-00-163-0143**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0