NSN 5962-00-163-6282



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-163-6282 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and medium speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Current-mode logic **Input Circuit Pattern:** 8 input **Case Outline Source And Designator:** T0-116 joint electron device engineering council **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 40.0 volts power source **Time Rating Per Chacteristic:** 20.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Diode matrix **Test Data Document:** 82577-3255002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

Sheir

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-00-163-6282

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0