

View Online at <https://aerobasegroup.com/nsn/5962-00-163-7127>

**Body Length:**

Between 0.330 inches and 0.350 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.050 inches and 0.080 inches

**Maximum Power Dissipation Rating:**

24.7 milliwatts

**Operating Temperature Range:**

-0.0 to 75.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and low power and asynchronous and resettable and synchronous and w/enable and positive outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Bit Quantity:**

4

**Design Function And Quantity:**

2 flip-flop, r-s-t input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

6.0 volts power source

**Time Rating Per Characteristic:**

60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

13499-351-7717 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0