## NSN 5962-00-165-2969

Linear Microcircuit - Page 1 of 1

**Demilitarization:**Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-165-2969 **Body Length:** 1.060 inches **Body Width:** 0.595 inches **Body Height:** 0.200 inches **Operating Tempurature Range:** -55.0 to 85.0 degrees celsius Storage Tempurature Range: -55.0 to 125.0 degrees celsius **Features Provided:** Hybrid and positive outputs **Inclosure Material: Plastic Inclosure Configuration:** Single-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 driver **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 37695-615157 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 pin Shelf Life: N/a **Unit Of Measure:**