## NSN 5962-00-166-4016

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-166-4016

View Online at https://aerobasegroup.com/nsn/5962-00-166-4016
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
93.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and high speed and darlington-connected and w/totem pole output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Triple 3 input
Design Function And Quantity:
3 gate, nand
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli