NSN 5962-00-166-5728

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-166-5728 **Body Length:** Between 0.365 inches and 0.375 inches **Body Width:** Between 0.245 inches and 0.252 inches **Body Height:** Between 0.115 inches and 0.125 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Adjustable and monolithic and positive outputs and programmable and w/buffered output **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 generator, function and 1 oscillator, voltage controlled **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 26.0 volts power source **Time Rating Per Chacteristic:** 20.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Yes - demil/mli

Fiig:

A458a0