NSN 5962-00-167-6312

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-167-6312 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 160.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and medium speed and w/enable and edge triggered **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 flip-flop, j-k, clocked **Case Outline Source And Designator:** T0-116 joint electron device engineering council **Time Rating Per Chacteristic:** 18.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level output Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0