## NSN 5962-00-167-6318

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-167-6318

Body Length:  Between 0.240 inches and 0.275 inches  Body Width:  Between 0.160 inches and 0.185 inches  Body Height:  Between 0.030 inches and 0.070 inches  Maximum Power Dissipation Rating:  110.0 milliwatts
Body Width:  Between 0.160 inches and 0.185 inches  Body Height:  Between 0.030 inches and 0.070 inches  Maximum Power Dissipation Rating:  110.0 milliwatts
Between 0.160 inches and 0.185 inches  Body Height:  Between 0.030 inches and 0.070 inches  Maximum Power Dissipation Rating:  110.0 milliwatts
Body Height:  Between 0.030 inches and 0.070 inches  Maximum Power Dissipation Rating:  110.0 milliwatts
Between 0.030 inches and 0.070 inches  Maximum Power Dissipation Rating:  110.0 milliwatts
Maximum Power Dissipation Rating: 110.0 milliwatts
110.0 milliwatts
On another Tanasanatura Barrara
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and medium speed and w/enable and edge triggered
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 flip-flop, j-k, clocked
Case Outline Source And Designator:
T0-85 joint electron device engineering council
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0