NSN 5962-00-168-9422

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-168-9422

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
87.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and ac coupled and medium speed and w/enable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
3 input
Design Function And Quantity:
1 flip-flop, j-k, clocked
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
80063-sm-a-569483 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Λ <i>4</i> 58a0