# NSN 5962-00-169-3826

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-169-3826

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

#### **Maximum Power Dissipation Rating:**

22.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and edge triggered and low power and presettable and w/clear

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Dual 4 input

#### Design Function And Quantity:

2 flip-flop, clocked and 2 flip-flop, d-type

#### Case Outline Source And Designator:

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### **Time Rating Per Chacteristic:**

125.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level

# output

## Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0