NSN 5962-00-172-5565

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-172-5565

Body Length:
Between 0.660 inches and 0.785 inches

Body Width:
Between 0.220 inches and 0.280 inches

Body Height:
Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:
300.0 milliwatts

Operating Tempurature Range:
+0.0/+75.0 degrees celsius

Storage Tempurature Range:

Features Provided:

-65.0/+150.0 degrees celsius

Adjustable and externally compensated and monolithic and positive outputs

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

7 input

Design Function And Quantity:

1 phase locked loop

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-12.0 volts $\,$ power source and 26.0 volts $\,$ power source

Time Rating Per Chacteristic:

20.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0