NSN 5962-00-172-8261

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-172-8261

Body Outside Diameter: Between 0.335 inches and 0.370 inches Body Height: 0.180 inches Maximum Power Dissipation Rating: 880.0 millivants Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -56.0/+125.0 degrees celsius Storage Tempurature Range: -56.0/+125.0 degrees celsius Storage Tempurature Range: -56.0/+125.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demil/mil Filig: Hassa0	
Body Height: 0.180 inches Maximum Power Dissipation Rating: 880.0 milliwatis Operating Tempurature Range: -55.01+125.0 degrees celsius Storage Tempurature Range: -56.01+126.0 degrees celsius Storage Tempurature Range: -56.01+126.0 degrees celsius Storage Tempurature Range: -56.01+126.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically seeled and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30,0 volts power source Test Data Document: 98214-538958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Body Outside Diameter:
0.180 inches Maximur Power Dissipation Rating: 800.0 millivents Operating Tempurature Range: -55.0/125.0 degrees celsius Storage Tempurature Range: -65.0/125.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-530856 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: Na Unit of Measure:	Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating: 880.0 milliwatts Operating Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure:	Body Height:
Second milliwatts Operating Tempurature Range: -55.04-125.0 degrees celsius Storage Tempurature Range: -65.04-150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hemetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	0.180 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Material: Glass and metal Inclosure Confliguration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 98214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	680.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Imput Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-539958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure:	Operating Tempurature Range:
-65.0+150.0 degrees celsius End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-538958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-55.0/+125.0 degrees celsius
End Application: Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Storage Tempurature Range:
Training aid type awards Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	-65.0/+150.0 degrees celsius
Features Provided: Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536956 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	End Application:
Monolithic and hermetically sealed and positive outputs and synchronous Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Training aid type awards
Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Features Provided:
Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Monolithic and hermetically sealed and positive outputs and synchronous
Inclosure Configuration: Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Inclosure Material:
Can Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Glass and metal
Input Circuit Pattern: 4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig:	Inclosure Configuration:
4 input Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Can
Design Function And Quantity: 1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Input Circuit Pattern:
1 demodulator and 1 modulator Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	4 input
Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Design Function And Quantity:
Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1 demodulator and 1 modulator
Voltage Rating And Type Per Characteristic: 30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Surface Treatment:
30.0 volts power source Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Tin
Test Data Document: 96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Rating And Type Per Characteristic:
96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	30.0 volts power source
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Test Data Document:
Terminal Type And Quantity: 10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	96214-536958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
10 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	10 pin
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A458a0	Fiig:
	A458a0