# NSN 5962-00-173-1427

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-173-1427

# **Body Length:**

Between 0.755 inches and 0.785 inches

## **Body Width:**

Between 0.265 inches and 0.291 inches

# **Body Height:**

Between 0.150 inches and 0.199 inches

# **Maximum Power Dissipation Rating:**

670.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed and high gain and low power and negative outputs and positive outputs and internally compensated

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

## **Input Circuit Pattern:**

Dual 2 input

# **Terminal Surface Treatment:**

Tin

#### Time Rating Per Chacteristic:

300.00 nanoseconds propagation delay time, low to high level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## Fiig:

A458a0