NSN 5962-00-175-4568

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-175-4568

| View Online at https://aerobasegroup.com/nsn/5962-00-175-4568 |
|---|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 175.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and positive outputs and medium speed and w/strobe |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 9 input |
| Design Function And Quantity: |
| 1 comparator, magnitude |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Time Rating Per Chacteristic: |
| 40.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level |
| output |
| Precious Material And Location: |
| Terminals gold and body gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 00752-374693 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

Fiig: A458a0

Demilitarization: Yes - demil/mli