## NSN 5962-00-175-8948

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-00-175-6946
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Features Provided:
Hybrid and hermetically sealed and negative outputs and positive outputs and high speed and w/field effect transistor switch
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 channel
Design Function And Quantity:
1 switch, analog and 1 switch, field effect transistor
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
00752-373726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli