NSN 5962-00-175-8958

Linear Microcircuit - Page 1 of 1

Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-175-8958 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** Between 0.265 inches and 0.291 inches **Body Height:** Between 0.130 inches and 0.199 inches **Maximum Power Dissipation Rating:** 670.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and high voltage and high gain and internally compensated and low power **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Case Outline Source And Designator:** T0-116 joint electron device engineering council **Terminal Surface Treatment:** Tin **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 25500-gr1-29 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:**